

RS 6000A

Reference Standard Series 3-Way

SPECIFICATIONS

ACOUSTIC & ELECTRICAL SPECIFICATIONS:

- Nominal Impedance: 6 ohms
- Power Rating: 35-200 watts RMS
- Sensitivity: 89dB @ 1 watt, 1 meter
- Crossover Frequencies: 600Hz and 5,000Hz
- Frequency Response: 42Hz-45kHz +/-3dB


PRODUCTION HISTORY

- Introduced in 1991
- Discontinued 1993
- Original Retail Price: \$179.00/pair


PHYSICAL SPECIFICATIONS:

- 1x - EMIT *k*TM Tweeter
- 1x - 2" (5cm) Polydome Midrange
- 2x - 10" (25.4cm) Polypropylene Woofers
- Dimensions: 36"H x 15"W x 10.25"D
92.75cm(H) x 38cm(W) x 26cm(D)
- Cabinet: Not Sold
- Grille: #026-3111
- Crossover: #015-3145
- Midrange Control: #145-0110
- Tweeter Control: #145-0103
- Logo: NLA


TECHNICAL INFORMATION



TWEETER
#902-3082
DIAPHRAGM
#751-3722



MIDRANGE
#902-3186
DIAPHRAGM
#751-2414



WOOFER
#902-2664

